



E4

Super High Speed Power Saving Overlock Machine
Power saving; Oil-proof




Suitable for light and heavy material



Oil-proof needle bar



Easy to operate



Single shaft drive; Stable and fast

Model	Functions	Needle	Needle No.	Thread No.	Needle Distance (mm)	Stitch Width (mm)	Stitch Length (mm)	Differential Ratio	Presser Foot Lifting Height (mm)	Max. Speed (s.p.m)	Volume (mm)	Weight (kg)
E4-2	Fabric Joint Sewing	DCx27 11#	1	2	-	6	3.8	0.7-2	3.5	5500	525x360x510	28/36
E4-02x250	Pocket Binding Seaming	DCx27 14#	2	4	5	5	3.8	0.7-2	3.5	5500	525x360x510	28/36
E4-3-02/233	Plain Seaming	DCx27 11#	1	3	-	4	3.8	0.7-2	5	5500	525x360x510	28/36
E4-3-82/233	Back Latching	DCx27 11#	1	3	-	4	3.8	0.7-2	5	5500	525x360x510	28/36
E4-3-12/233	Blindstitch Hemming	DCx27 11#	1	3	-	4	3.8	0.7-2	5	5500	525x360x510	28/36
E4-3-32R2/223	Baby Overlock Stitch	DCx27 9#	1	3	-	1.5	3.8	0.7-2	5	5500	525x360x510	28/36
E4-WF-3-02/213	Non-woven Material	DCx27 14#	1	3	-	4	8.5	-	5	5500	525x360x510	28/36
E4-4-M03/333	Plain Seaming	DCx27 11#	2	4	2	4	4.6	0.7-2	5.5	5500	525x360x510	28/36
E4-4-83/323	Back Latching	DCx27 11#	2	4	2	4	4.2	0.7-2	5.5	5500	525x360x510	28/36
E4-4-M03/333/H/M	Heavy Duty	DCx27 11#	2	4	2	4	4.6	0.7-2	6	5500	525x360x510	28/36
E4-MJ-4-53/233	Towel Ending	DCx27 11#	2	4	2	4	3.8	0.7-2	5	5500	525x360x510	28/36
E4-5-53/233	Strip Attach Seaming	DCx27 14#	2	5	3	4	3.8	0.7-2	5	5500	525x360x510	28/36
E4-5-02A/233	Light Material	DCx27 11#	2	5	3	4	3.8	0.7-2	5	5500	525x360x510	28/36
E4-5-03/233	5x5 Stitch	DCx27 14#	2	5	5	5	3.8	0.7-2	5	5500	525x360x510	28/36
E4-5-03/333	3x4 Stitch	DCx27 14#	2	5	3	4	3.8	0.7-2	5	5500	525x360x510	28/36
E4-5-A04/435	Extra Heavy Duty	DCx27 19#	2	5	5	6	5	0.8-1.5	7	5500	525x360x510	28/36
E4-6-03/333	Plain Seaming	DCx27 11#	3	6	3x2	4	3.8	0.7-2	5	5500	525x360x510	28/36