





C4

High Speed Automatic Overlock Machine
Full-automatic; Electronic device; Oil-proof; Voice guide



High efficiency



Intelligent recognition of fabric thickness



Voice guide; One key to reset



Available to narrow and wide edge

Model	Functions	Needle	Needle No.	Thread No.	Needle Distance (mm)	Stitch Width (mm)	Stitch Length (mm)	Differential Ratio	Presser Foot Lifting Height (mm)	Max. Speed (s.p.m)	Volume (mm)	Weight (kg)
C4-02x250	Pocket Binding Seaming	DCx27 14#	2	4	5	5	3.8	0.7-2	3.5	7000	525x360x510	33/41
C4-3-02/233	Plain Seaming	DCx27 11#	1	3	-	4	3.8	0.7-2	5	7000	525x360x510	33/41
C4-3-12/233	Bottom Hemming	DCx27 11#	1	3	-	4	3.8	0.7-2	5	7000	525x360x510	33/41
C4-3-32R2/223	Narrow Stitch Seaming	DCx27 9#	1	3	-	1.5	3.8	0.7-2	5	7000	525x360x510	33/41
C4-WF-3-02/213	Non-woven Fabric	DCx27 14#	1	3	-	4	8.5	-	5	7000	525x360x510	33/41
C4-4-M03/333	Plain Seaming	DCx27 11#	2	4	2	4	4.6	0.7-2	5.5	7000	525x360x510	33/41
C4-4-M03/333/H/M	Heavy Duty	DCx27 11#	2	4	2	4	4.6	0.7-2	6	7000	525x360x510	33/41
C4-4-M03/333/AD	Adjustable Side Stitch Width	DCx27 11#	2	4	2	4-8	4.6	0.7-2	5.5	7000	525x360x510	33/41
C4-MJ-4-53/233	Towel Ending	DCx27 11#	2	4	2	4	3.8	0.7-2	5	7000	525x360x510	33/41
C4-5-53/233	Strip Attach Seaming	DCx27 14#	2	5	3	4	3.8	0.7-2	5	7000	525x360x510	33/41
C4-5-03/233	5x5 Stitch	DCx27 14#	2	5	5	5	3.8	0.7-2	5	7000	525x360x510	33/41
C4-5-03/333	3x4 Stitch	DCx27 14#	2	5	3	4	3.8	0.7-2	5	7000	525x360x510	33/41
C4-5-A04/435	Extra Heavy Duty	DCx27 19#	2	5	5	6	5	0.8-1.5	7	7000	525x360x510	33/41
C4-6-03/333	Plain Seaming	DCx27 11#	3	6	3x2	4	3.8	0.7-2	5	7000	525x360x510	33/41

Note: H/M: suitable for heavy and medium material. SD device is available (start and end suction device); volume: 525x360x640 (mm), weight 33/44 (kg).