



## A6F

Computerized Needle Feed Lockstitch Machine  
Full-automatic; Needle feed; No thread tail; Semi-dry




## A5

Thread Cleanness Computerized Lockstitch Machine  
Full-automatic; No thread tail; Semi-dry



Needle feed; Avoid of layers offset



No thread tail




Touchable panel





Large space

Model	Needle	Thread No.	Stitch Length (mm)	Presser Foot Lifting Height (mm)	Max. Speed (s.p.m)	Light/ Medium Heavy Duty	Volume (mm)	Weight (kg)
A6F	DBx1 11-18#	2	4.5	5-13	4000	√	695x315x670	46/53
A6F-N	DBx1 11-18#	2	4.5	5-13	4000	√	695x315x670	46/53

Note: auto thread trimming, auto reverse, auto presser foot lifter, electronic thread tension are equipped as standard.  
N: less bird-nest device, pneumatic and electronic suction device are optional.



Initial sewing without bird nest; Short thread tail after trimming



Semi-dry



Sealed oil pan

Model	Needle	Thread No.	Stitch Length (mm)	Presser Foot Lifting Height (mm)	Max. Speed (s.p.m)	Light/ Medium Heavy Duty	Volume (mm)	Weight (kg)
A5	DBx1 11-18#	2	5	5-13	5000	√	645x248x550	40/46
A5-N	DBx1 11-18#	2	5	5-13	5000	√	645x248x550	40/46

Note: auto thread trimming, auto reverse, auto presser foot lifter, electronic thread tension are equipped as standard.  
N: less bird-nest device, pneumatic and electronic suction device are optional.